



MSI MAG A1000GL PCIE5 virtalähdeyksikkö 1000 W 24-pin ATX ATX musta



Tuotemerkki : MSI

Tuotekoodi: MAG A1000GL PCIE5

Tuotteen nimi : MAG A1000GL PCIE5

MSI MAG A1000GL PCIE5. Kokonaisteho: 1000 W, AC-syöttöjännite: 100 - 240 V, AC-syöttötaajuus: 50/60 Hz. Emolevyn virtaliitin: 24-pin ATX, Emolevyn virtapiuhan pituus: 60 cm, SATA-virtakaapelin pituus: 150,500 mm. Tarkoitus: PC, Virransyöttöyksikön mitat: ATX, 80 PLUS certification: 80 PLUS Gold. Tuotteen väri: musta, Jäähdytyksen tyyppi: Aktiivinen, Tuulettimen halkaisija: 13,5 cm. Tuotteen leveys: 150 mm, Tuotteen syvyys: 150 mm, Tuotteen korkeus: 86 mm

Power		Ports & interfaces	
Total power *	1000 W	EPS power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	PCI Express power connectors (6+2 pin)	4
AC input frequency	50/60 Hz	PCI Express power connectors (16-pin)	1
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Number of +12V rail(s)	1	Performance	
Combined power (+3.3V)	120 W	80 PLUS certification *	80 PLUS Gold
Combined power (+12V)	999.6 W	Purpose *	PC
Combined power (+5V)	120 W	Power supply unit (PSU) form factor *	ATX
Combined power (-12V)	3.6 W	ATX version	3.1
Combined power (+5Vsb)	15 W	Bearing technology	FDB
Max output current (+3.3V)	22 A	Design	
Max output current (+12V)	83.3 A	Product colour	Black
Max output current (+5V)	22 A	Cooling type	Active
Max output current (-12V)	0.3 A	Fan diameter	13.5 cm
Max output current (+5Vsb)	3 A	Number of fans	1 fan(s)
Efficiency	90%	Fan speed	500 - 1800 RPM
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Illumination	✗
Ports & interfaces		On/off switch	✓
Motherboard power connector *	24-pin ATX	Weight & dimensions	
Motherboard power cable length	60 cm	Width	150 mm
Number of SATA power connectors	12	Depth	150 mm
SATA power cable length	150,500 mm	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	1	Weight	169 g
Peripheral (Molex) power cable length	450,500 mm	Technical details	
EPS power connector (8-pin)	✗	Sustainability compliance	✓
		Other features	
		Fan's mean time to failure (MTTF)	150000 h



4711377142243

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-MAR-2025. Prints or copies of Information are only valid on the printed Publication date